

# Oxygen and Medical Air Pressure Compensated Flowmeters (ANSI)



Oxygen



Twin



Medical Air



Available "Second Look" Connector - for enhanced safety (as shown)

## DESCRIPTION AND APPLICATION

The Pressure Compensated Flowmeter is designed to meet strict standards of durability and precision. The base is constructed of solid brass and full body gas specific colored labeling\*.

Flowmeters are available with a wide variety of options including DISS power outlets and twin flowmeter configurations. They are also available with an optional plastic DISS tubing nipple and a multitude of wall adapters.

### 0-15 LPM Oxygen and Medical Air Flowmeters

- Provides accurate gas flow measurement and control within a range of 0-15 LPM
- For use in a variety of respiratory therapy clinical applications
- Flush setting delivers a minimum of 50 LPM
- Supply pressure of 50 psi

### LoFlo 3.5 LPM Oxygen Flowmeter

- Provides highly accurate gas flow measurement and control within a range of 0.125-3.5 LPM
- For use in low flow applications
- Flush setting delivers a maximum of 45 LPM
- Supply pressure of 50 psi

### Neonatal and Pediatric 0-200 CCM & 0-1 LPM Flowmeter

- Provides highly accurate gas flow measurement and control within a range of 25-200 CCM (200 CCM model) & 0.1-1 LPM (0-1 LPM model)
- Neonatal and Pediatric identification (stork label)
- For use in Neonatal, Pediatric, and other low flow applications
- Flush setting delivers a maximum of 500 CCM (200 CCM model) & 2.5 LPM (0-1 LPM model)
- Supply pressure of 50 psi
- High precision glass ball ensures clear readability

### Lo-High Duplex Oxygen Flowmeters

- Consists of a "Y" adapter\*\* with a LoFlo 3.5 flowmeter on the left branch and a 0-15 LPM flowmeter on the right branch
- Configuration allows the clinician better versatility based on clinical demand.

## Twin Oxygen Flowmeters

- Consists of two Pressure Compensated Flowmeters mounted onto a "Y" adapter
- Features compact design yet can accommodate double humidifiers and nebulizers when necessary

## FEATURES AND BENEFITS

### Durable

- Impact resistant flow tube and shroud
- Solid brass body with full body gas specific colored labeling\*.
- D-Shape knob helps prevent striping

### Precise

- Pressure compensated, accurate flow readings
- Flow tubes individually tested for accuracy
- High precision glass ball ensures clear readability (0-1 LPM, 0-200 CCM)

### Safety features

- White background improves visibility
- Knob and needle valve have a stop to help prevent entire component from unscrewing completely
- Color coded to help prevent cross connections

### Optional

- "Second Look" Connector (clear) available on all configurations.
- Traditional color coded connectors available on all configurations

(\*excluding Neonatal and Pediatric models)

## SPECIFICATIONS

### Calibration Pressure and Temperature

- 50 psig (320 kPa) and 70°F (21°C) as specified on the flow tube label

### Maximum Pressure

- 100 psig (690 kPa)

### Power Outlet Flow Rate (Power Outlet Models Only)

- Minimum 150 LPM with adequate supply flow

Gas	Scale	Increments	Accuracy Averages	Max. Flood/Flush
Oxygen	<b>0-200 CCM</b>	25 CCM (starts at 25 CCM)	+/- 20 CCM	500 CCM
Oxygen	<b>0-1 LPM</b>	0.1 LPM (starts at 0.1 LPM)	+/- 0.1 LPM	2.5 LPM
Oxygen	<b>0-3.5 LPM</b> LoFlo	0.125 LPM (from 0.125 to 1 LPM) 0.25 LPM (from 1 to 3.5 LPM)	+/- 0.125 LPM or +/- 10% of reading (whichever is greater)	45 LPM

Gas	Scale	Increments	Accuracy Averages	Min. Flood/Flush
Oxygen / Medical Air	<b>0-15 LPM</b>	0.5 LPM (from 1 to 5 LPM) 1 LPM (from 5 to 15 LPM)	+/- 0.5 LPM or +/- 10% of reading (whichever is greater)	50 LPM

\*Specifications are nominal, subject to change without notice.

## SHIPPING INFORMATION

	Flowmeter 0-15 & 0-3.5 LPM	Flowmeter 0-1 LPM	Flowmeter 0-200 CCM	Twin Flowmeter
<b>Weight**</b> **Less fittings and adapters	5.6 oz (159 g)	5.6 oz (159 g)	5.6 oz (159 g)	16 oz (454 g)
<b>Dimensions</b>	Height: 5.5in (139mm) Width: 1.1in (28mm) Depth: 3.4in (86mm)	Height: 5.5in (139mm) Width: 1.1in (28mm) Depth: 3.4in (86mm)	Height: 5.5in (139mm) Width: 1.1in (28mm) Depth: 3.4in (86mm)	Height: 5.5in (139mm) Width: 6in (152mm) Depth: 3.5in (89mm)
<b>Package Dimensions</b>	Height: 8in (203mm) Width: 4.5in (114mm) Depth: 3in (76mm)	Height: 8in (203mm) Width: 4.5in (114mm) Depth: 3in (76mm)	Height: 8in (203mm) Width: 4.5in (114mm) Depth: 3in (76mm)	Height: 6.5in (165mm) Width: 10.25in (260mm) Depth: 7.75in (197mm)

## PARTS CONFIGURATION

<b>Adapter</b>	
No Adapter with 1/8" NPT Female	00
Diamond	01
DISS Hand-I-Twist (HIT)	02
DISS Nut & Gland	03
Schrader®	04
Chemetron® Rectangle Striker (NCG) (AIR)	05
Chemetron® Round Striker (NCG) (OXYGEN)	06
Puritan Bennett®	07
O.E.S. Twist	08
O.E.S. Med Star®	09
DISS Male	14

**77XX - XXXX - 9XX**

Clear Tubing Nipple Nut & Gland	31
Tubing Nipple Nut & Gland	21
DISS Fitting	07

<b>Flowmeters (Oxygen)</b>	
200 CCM O <sub>2</sub> with DISS fitting	1316
0-1 LPM with O <sub>2</sub> DISS fitting	1309
LoFlo 3.5 with O <sub>2</sub> DISS fitting	1305
0-15 LPM O <sub>2</sub> with O <sub>2</sub> DISS fitting	1260
0-1 LPM with O <sub>2</sub> DISS fitting and O <sub>2</sub> power outlet	1310
LoFlo 3.5 with O <sub>2</sub> DISS fitting and O <sub>2</sub> power outlet	1306
0-15 LPM O <sub>2</sub> with O <sub>2</sub> DISS fitting and O <sub>2</sub> power outlet	1261
<b>Twin Flowmeters (Oxygen)</b>	
0-1 LPM Twin with O <sub>2</sub> DISS fitting	1311
LoFlo 3.5 Twin with O <sub>2</sub> DISS fitting	1307
0-15 LPM O <sub>2</sub> Twin with O <sub>2</sub> DISS fitting	1262
0-1 LPM Twin with O <sub>2</sub> DISS fitting and O <sub>2</sub> power outlet	1314
LoFlo 3.5 with O <sub>2</sub> DISS fitting and O <sub>2</sub> power outlet	1308
0-15 LPM Twin with O <sub>2</sub> DISS fitting and O <sub>2</sub> power outlet	1263
<b>Flowmeters (Medical Air)</b>	
0-15 LPM Air with O <sub>2</sub> DISS fitting	1264
0-15 LPM Air with O <sub>2</sub> DISS fitting and Air power outlet	1266
<b>Lo-High Duplex (Oxygen)</b>	
LoFlo 3.5 & 0-15 LPM	1502
LoFlo 3.5 & 0-15 LPM with O <sub>2</sub> power outlet	1503



© 2018 Ohio Medical, LLC. This document contains information that is proprietary and confidential to Ohio Medical, LLC. Use of this information is under license from Ohio Medical, LLC. Any use other than that authorized by Ohio Medical, LLC is prohibited. Ohio Medical and the Ohio Medical logo are registered trademarks of Ohio Medical, LLC. Chemetron and Med Star are registered trademarks of Allied Healthcare Products. Puritan Bennett is a registered trademark of Covidien LP. Schrader is a registered trademark of Schrader-Bridgeport International.

**Ohio Medical LLC**  
1111 Lakeside Drive, Gurnee, IL 60031 USA  
Phone: 1.866.549.6446  
[www.ohiomedical.com](http://www.ohiomedical.com)  
255441 (Rev. 10) 04/2018