

MiniOX[®] 200 Oxygen Analyzer

The MiniOX 200 was designed with simplicity and portability in mind. This analyzer quickly adapts for use in tubing applications and is ideal for checking oxygen percent accuracy in line or on oxygen concentrators. The patented ergonomic design fits comfortably in your hand and has a two-year warranty.

PART NUMBERS

| | |
|---|--------|
| MiniOX 200 | 600200 |
| MiniOX 200 (International) | 600201 |
| MiniOX 250 O ₂ Internal Sensor | 606930 |

PACKAGE CONTENTS

- Analyzer
- Batteries
- Internal O₂ Sensor
- Barbed Adapter with tubing
- 15 mm Tee Adapter
- Flow Diverter
- Lanyard
- Manual

ACCESSORIES



Patented ergonomic design fits comfortably in your hand.

1. **Large LCD**
Easy-to-read characters
2. **Calibration Reminder**
Reminds once a week
3. **One-Touch Calibration**
Auto calibrate to room air or 100% Oxygen
4. **ON/OFF Button**
One-touch ON and OFF
5. **Patented Ergonomic Design**
Fits comfortably in your hand
6. **Low Battery Indicator**
5,000+ hours of battery life
7. **Internal O₂ Sensor**
MiniOX 250, 0-100% Oxygen, 24-month warranty
(not shown)



CE
0123

SPECIFICATIONS

| | |
|-----------------------------|--|
| Sensor Type | Galvanic fuel cell |
| Measurement Range | 0-100% Oxygen |
| Resolution/Display | 0.1% Oxygen |
| Temperature | Operating: 59°- 104°F (15° - 40°C), Storage: 5°- 122°F (-15° to 50°C) |
| Operating Humidity Range | 0-95% RH non-condensing |
| Oxygen Measurement Accuracy | ±3% Actual Oxygen level over full operating temperature range |
| Sensor Connection | M16 x 1 Thread |
| Sensor Operating Life | > 900,000 Oxygen percent hours, minimum 2 years in typical applications |
| 90% Response Time | < 15 Seconds @ 23°C |
| Low-Battery Indicator | "BAT" icon displayed on LCD |
| Power Requirement | Two AA Alkaline Batteries (2 x 1.5 volts) |
| Calibration Reminder | One week timer started with every calibration, "CAL" icon displayed on LCD |
| Weight | 0.40 lb (170 g) |
| Dimensions | 3.0" x 3.75" x 1.5" (76 x 95 x 38 mm) |

© 2020 Ohio Medical, LLC. All rights reserved. This document contains information that is proprietary and confidential to Ohio Medical, LLC. Use of this information is under license from Ohio Medical, LLC. Any use other than that authorized by Ohio Medical, LLC is prohibited. Ohio Medical, MiniOX, and the Ohio Medical logo are registered trademarks of Ohio Medical, LLC. Maxtec is a trademark of Maxtec, LLC.



Distributed by:
Ohio Medical LLC
1111 Lakeside Drive
Gurnee, IL 60031 USA
866.549.6446 | ohiomedical.com
550624 (Rev. 2) 10/2020