






care-e-vac PORTABLE SUCTION UNITS



	care-e-vac <i>Plus</i>	care-e-vac <i>EMS</i>	care-e-vac <i>C/I</i>
			
With reusable jar, 800cc	5320214	5320216	5320212
With disposable jar, 1200cc	5320215	5320217	5320213
Power supply	12 VDC Battery	12 VDC Battery	100/240 VAC 12 VDC Battery
Free air suction flow	30 L/min	30 L/min	5 L/min Continuous/Intermittent
Maximum vacuum	84 kPa 630 mmHg	84 kPa 630 mmHg	20 kPa 150 mmHg
Electric power	85 W	85 W	35 W (AC) 30 W (DC)
Internal battery	12 V - 4.5 Ah Pb-Acid 65 min	12 V - 4.5 Ah Pb-Acid 65 min	12 V - 4.5 Ah Pb-Acid 120 min
AC Internal battery charger	-	-	✓
AC/DC External battery charger	✓	Optional	-
10 g tested wall bracket including 12 V power supply	Optional	✓	Optional
Cable 12/24 V for ambulance	✓	✓	✓
Bacteria filter	✓	✓	✓
Noise level	60 dBA	60 dBA	46 dBA
Weight	9.26 lbs	9.26 lbs	7.1 lbs
Dimensions	Height	Width	Depth
	9.85"	15.75" with PC1 jar 16.75" with disposable jar	6.3"
Space required to mount in an ambulance, with 10 g bracket	11-1/2"	16" with PC1 jar 17" with disposable jar	6-5/8"
Packaged Dimensions	11-1/2"	18"	8-1/4"

- ✓ included with the device
- not available for the device

care-e-vac

High quality and high performance portable suction units

Due to their versatility, **Care-e-vac PLUS** and **Care-e-vac EMS** can be used throughout hospitals, on crash carts, and in ambulances for emergency suction applications.

Continuous-Intermittent **Care-e-vac C/I** is specifically developed for gastric suction and other therapies requiring precise low vacuum.

The rear mounting system is tested to resist accelerations and decelerations of 10 g in longitudinal, transverse and vertical direction, providing secure wall mount installation for crash carts and ambulances.

The powered wall bracket included with **Care-e-vac EMS** provides convenient battery charging whenever the device is mounted.

Key Features:

- > Piston type suction pump on **Care-e-vac PLUS** and **Care-e-vac EMS**.
- > Membrane type suction pump on **Care-e-vac C/I**.
- > All models oil-free and maintenance-free.
- > Analog vacuum gauge range of 0-760 mm Hg on **PLUS** and **EMS** models.
- > Digital vacuum display range of 0-200 mmHg on the **C/I** model.
- > Ergonomical case is made from durable ABS material
- > Water-proof ON/OFF switch with guard protects against accidental activation and damage.
- > Rechargeable Battery (Pb-Acid) and LED battery level indicator included on all models.
Battery life up to 65 min from full charge, up to 120 min for C/I model
Recharge time approximately 5 hours to full charge.
- > **Care-e-vac PLUS** and **Care-e-vac EMS** LED indicator lights: Power ON, Charging, and battery status.
User controls: Vacuum control knob
- > **Care-e-vac C/I** LED Indicator lights: Power On, vacuum level, battery status, Intermittent program status.
User controls: Vacuum control knob and Intermittent program control knob.
- > Includes bacteria filter with connecting tubing and 3m patient suction tubing.
- > Optional reusable polycarbonate suction jar (1 L and 2 L) with overflow protection, autoclavable up to 121°C / 250°F.
- > Optional disposable rigid canister (1200cc) and holder with overflow protection and filter.



care-e-vac PLUS



care-e-vac EMS



care-e-vac C/I

CARE-E-VAC ACCESSORIES

Part Numbers	
4320324	Wall bracket, Basic
4320321	Wall bracket 10G
4320320	Wall bracket 10G + DC
4320025	Mobile trolley, 5 caster
4320313	Ring Bracket, Disposable Canister
0321-5120-800	Disposable Collection Canister, 1200cc
4383044	1L Reusable Collection Jar PC
4383054	2L Reusable Collection Jar PC (not shown)
4320038	Power cable 12/24 V
4320039	AC Charger, 120-12 V
3320223	Transport bag in nylon (not shown)
0940023	PVC Suction Tube, 8mmx13mm (not shown)
4320015	Bacteria filter, pack (10 units)
4320050	Yankauer w/ 2m suction tube
4320325	Slide bracket adapter, 35mm to 40mm (not shown)



4320324



4320320/ 4320321



0321-5120-800



4320038



4320039



4383044



4320015



4320050



4320313



4320325